



2111475-7 | E-SERIES JACK,UTP,C6,RED

Body Features

110 Block Material Polycarbonate

Configuration Features

Keyed No
Number of Positions 8
Wiring Pattern Universal

Contact Features

Contact Base Material Beryllium copper
Contact Mating Area Plating Material Gold
Contact Mating Area Plating Thickness 50.00 μin | 1.27 μm

Dimensions

Cable Diameter (Max) 5.8 mm | 0.2 in
Conductor Outside Diameter 0.057 in | 1.45 mm
Solid Wire Range .51 mm² | .65 mm² | 22 AWG | 24 AWG
Stranded Wire Range .14 mm² | .2 mm² | 24 AWG | 26 AWG

Housing Features

Housing Color Red
Housing Material Polycarbonate

Industry Standards

UL Flammability Rating UL 94V-0

Mechanical Attachment

Mounting Type KL Series Faceplate | Panel Mount

Packaging Features

Packaging Method Poly Bag

Product Availability

Region Asia | Latin America | North America

Product Type Features

2111475-7 | E-SERIES JACK, UTP, C6, RED

Product Type	Connector - Modular
Connector Style	Jack
Jack Type	RJ45
Connector Type	Connector Assembly
Dust Cover	Without
Performance Category	Category 6
Shielded	No

Termination Features

Termination Method to Wire/Cable	Insulation Displacement Crimp (IDC)
Termination Style	SL Termination Tool

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant